

NOX URANO PRO

80 PLUS BRONZE CERTIFIED POWER SUPPLY



FEATURES

- 80 PLUS Bronze Certified, ensuring a minimum efficiency of 85%
- ATX with Active PFC
- Double-sided copper PCB
- Extra-long flat cables
- Auto-voltage input 100-140V
- OVP, UVP, SCP, OPP, OTP & NLP protections
- Extra-long flat cables
- Ultra-silent 120 mm fan
- Single +12V rail
- Dimensions: 150 x 140 x 86 mm

VOLTAGES

550W	AC INPUT		100-240 Vac, 60-50 Hz, 12.5-6.3A				
	DC OUTPUT		+5V	+3.3V	+12V	-12V	+5VSB
	Max. Output Current		15A	15A	45A	0.3A	2.5A
	Max. Combined Wattage		100W		540W	3.6W	12.5W
	Maximum Power		550W				

650W	AC INPUT		100-240 Vac, 60-50 Hz, 12.5-6.3A				
	DC OUTPUT		+5V	+3.3V	+12V	-12V	+5VSB
	Max. Output Current		15A	15A	54A	0.3A	2.5A
	Max. Combined Wattage		100W		648W	3.6W	12.5W
	Maximum Power		650W				

750W	AC INPUT		100-240 Vac, 60-50 Hz, 12.5-6.3A				
	DC OUTPUT		+5V	+3.3V	+12V	-12V	+5VSB
	Max. Output Current		15A	15A	62A	0.3A	2.5A
	Max. Combined Wattage		100W		744W	3.6W	12.5W
	Maximum Power		750W				

850W	AC INPUT		100-240 Vac, 60-50 Hz, 12.5-6.3A				
	DC OUTPUT		+5V	+3.3V	+12V	-12V	+5VSB
	Max. Output Current		15A	15A	70A	0.3A	2.5A
	Max. Combined Wattage		100W		840W	3.6W	12.5W
	Maximum Power		850W				

CONNECTORS

	1x MB ATX 20+4 pin Motherboard		1x (550W & 650W) 2x (750W & 850W) EPS 12V 4+4 CPU		2x (550W & 650W) PCI Express 6+2 pin
	4x (750W & 850W) PCI Express 6+2 pin		4x SATA 4 pin		2x Molex 4 pin

PN NXURPRO850BZ
EAN 8436587975530

PN NXURPRO750BZ
EAN 8436587975547

PN NXURPRO650BZ
EAN 8436587975554

PN NXURPRO550BZ
EAN 8436587975561

NOX
nox-xtreme.com

